



Specifications

Display/Speaker	Language
LCD Display: 4.3" TFT high-definition graphical interface	Multi Language, English, French, Spanish, Arabic,
Speaker: Voice Prompt (language can be selected)	etc., for more than 40 languages can be selected
Technical Specifications Capacity	Environment
Face capacity: 700 Fingerprint capacity: 3,000 ID Card Capacity : 10,000	Operation temperature: 0 ~ 45
Log capacity: 100,000	Operation humidity: 20% ~ 80%
Verification/Identification	Verification/Identification
Verification speed(1:1): ≤ 0.5s	FRR: ≤ 0.01%
Identification speed(1:N): ≤ 1s	FAR: ≤ 0.0001%
Power Supply	Machine Size
Power: 110/220VAC ~ 12VDC	180(L)*125(W)*50(H)mm
Communication	Attendance status
TCP/IP, RS232/485, USB Host*2, Wiegand out	Check in, Check out, Break in, Break out, OT in, OT out
Standard Function	Customize Function
High definition infrared camera; 6 user-defines function keys; Built-in relay, simple access control, door sensor; Dismantlement alarm, break-in alarm, duress alarm; Scheduled bell, Workcode, SMS, T9 input, DST, Self inquiry, Photo-ID, Extendable scheduled bell.	Webserver, Li-battery, 14-pin code, Printer output; ID reader, Mifare reader, Wifi, GPRS

Diagram

Standalone

